



Brewery Fittings

Draft beer system consists of myriads of components – all brought together and connected using different kinds of caps, clamps, valves, etc. Specialized fittings such as Tri-clover connectors, Camlock adapters of different types are part of this category along with tail-pieces.

PRODUCT	PART NO.	DESCRIPTION	SIZE	TYPE
	C6565	Heavy Duty Stainless Steel Tri-Clover Fitting – 1.5" TC Clamp <ul style="list-style-type: none"> Fits 1.5 Inch Tri-clamp Suitable for all other homebrew stuff sanitary fittings; Easy tighten thumb screw Flange Size: 50.5MM Does NOT come with silicon gaskets 	1.5" Tri-Clover	1.5" TC Clamp
	C6566	Stainless Steel 1/4" Hose Barb to 1.5" TC Cap <ul style="list-style-type: none"> Adapter for connecting pipes or fittings of different types Designed for use with 1/4" ID tubing Barbed fitting for a tight seal on hoses when used with a hose clamp (not included) 	1/4" OD Hose Barb	Tri-Clover Hose Barb
	C6564	Stainless Steel Tri-Clover Fitting – 1.5" TC x 1/2" Male NPT <ul style="list-style-type: none"> Barbed Adapter for connecting pipes or fittings of different types Suitable for 1.5" tri clamp / clover / sanitary fitting Used for 1/2" Female NPT hardware 	1/2" Male NPT	1.5" Tri-Clover NPT
	C6613x10	Tri-Clamp Gasket – 1/2" <ul style="list-style-type: none"> Made of flexible and durable rubber. Makes the connection tight and ensures that there are no leaks. Perfect for tri clover brewery fitting of 1/2 inch. 	1/2"	Tri-Clamp Gasket
	C5208	1.5" TC Shank for Sampling Beer Faucet <ul style="list-style-type: none"> Easily fits with US Tap Easy to Clean it Installation is easy and quick also 	1.5" TRI CLAMP	Shank
	C5206	Tri-Clamp Blank <ul style="list-style-type: none"> Material:Stainless Steel High Pressure Durable Corrosion resistance and high temperature resistance Used for permanent sealing Easy to use Suitable for use in food, beverage, and dairy applications 	1.5" TRI CLAMP	Disk
	C3587	Ferrule Gasket For 1.5" Tri-Clover <ul style="list-style-type: none"> Made from food-grade silicone material. Features a smooth micro-finish for smoother operation. It is meant to be used with any 1.5" TC hardware. 	1.5" Tri-Clover	Tri-Clover Gasket
	C6612	TC Tailpiece for 1/2" Vinyl Hose – Stainless Steel 304 <ul style="list-style-type: none"> Made from Stainless Stainless 304 Grade. Compatible tailpiece for gas or beer tubings Used for 1/2" Vinyl Hose. Easy to fix and connect. 	1/2" Tube ID	TC Tailpiece

PRODUCT	PART NO.	DESCRIPTION	SIZE	TYPE
	C6563	Stainless Steel Camlock Adapter Type F – Male Camlock x 1/2" Male NPT <ul style="list-style-type: none"> Cam lock cam-and-groove adapter (plug) One male groove adapter end for connecting to female cam couplers and one NPT female threaded end for connecting to an NPT male threaded connection (Type F) No tools are needed 	1/2" Male NPT	Camlock Type F
	C6562	Stainless Steel Camlock Adapter Type A – Male Camlock x 1/2" Female NPT <ul style="list-style-type: none"> Assembly with female coupler to build connection between equipment One end male adapter; one end NPT female thread Commonly attached to pumps, plate chillers, and stationary brewing equipment 	1/2" Female NPT	Camlock Type A
	C6561	Stainless Steel Camlock Type C – Female Camlock x 1/2" Barb <ul style="list-style-type: none"> Use this barbed fitting to connect onto a male camlock. Add hose to your barb for quick connecting and disconnecting when you need it. Barb is 3/8" ID for very little reduction in flow 	1/2" OD Hose Barb (3/8"ID)	Camlock Type C
	C5233	3" Length Drop-In Thermowell(1.5") <ul style="list-style-type: none"> Compatible 3" Tri Clamp Thermowell Commonly used with 1.5" RIMS tube when a stock sensor that can't be immersed needs to be used 3/8" Thermowell welded into 1"1.5" Tri Clover Compatible Cap Also Available in different sizes	3"	Thermowell
	C5234	6" Length Drop-In Thermowell(1.5")	6"	Thermowell
	C5235	12" Length Drop-In Thermowell(1.5")	12"	Thermowell
	C5236	16" Length Drop-In Thermowell(1.5")	16"	Thermowell
	C5237	20" Length Drop-In Thermowell(1.5")	20"	Thermowell
	C5238	24" Length Drop-In Thermowell(1.5")	24"	Thermowell
	C5244	4" Length Thread-In Thermowell <ul style="list-style-type: none"> PP material is more environment protective 304 stainless steel strength and resistance to corrosion Used for food, beverage, and dairy applications Suitable for long-term use, not easy to damage and not corrupt Also Available in different sizes	4"	Thermowell
	C5245	6" Length Thread-In Thermowell	6"	Thermowell
	C5246	12" Length Thread-In Thermowell	12"	Thermowell
	C5247	20" Length Thread-In Thermowell	16"	Thermowell
	C5203	5/8" BSP X 1.5" Tri Clamp Connection <ul style="list-style-type: none"> 1" T.C X 5/8" BSP for Python Tubing Tri Clamp Plate ID: 5/16" Tri Clamp Plate OD: 2" 	5/8" BSP	1.5" TRI CLAMP
	C5207	Tri Clamp Gas and Liquid In Fitting <ul style="list-style-type: none"> Made from Stainless Stainless 304 Grade. Allows you to attach a gas ball lock disconnect to a 1.5"TC port. It is also excellent for use with carbonation stones and draw lines. 	1.5" TRI CLAMP	Liquid
	C5207.50	Tri Clamp Gas In Fitting-Liquid Inlet		Liquid
	C5207.51	Tri Clamp Gas In Fitting-Gas Inlet		Gas

With Krome's wide range of brewery fittings, You'll get everything from caps to clamps to valves and hoses.

PRODUCT	PART NO.	DESCRIPTION	SIZE	TYPE
	C5217	15-PSI Tank Breather (1.5") <ul style="list-style-type: none"> • Material: 304 Stainless Steel • Clamps to a 1.5" Tri Clover Compatible port. • Releases pressure at 15 psi and breaks a vacuum at 1.5 PSI. • Flange Outside Diameter: 1.984" 	1.5"	15 PSI
	C5218	30-PSI Tank Breather (1.5") <ul style="list-style-type: none"> • Material: 304 Stainless Steel • Clamps to a 1.5" Tri Clover Compatible port. • Releases pressure at 30 psi and breaks a vacuum at 1.5 PSI. • Flange Outside Diameter: 1.984" 	1.5"	30 PSI
	C6494	WELDLESS FLEX SIGHTGLASS <ul style="list-style-type: none"> • This level indicating accessory takes the guess work out of determining how much liquid is in any of your hot side brewing vessels • Helps to measure strike and sparge water volumes. • Also useful in boil kettles to measure pre and post boil volumes. 		Flex Sight glass
	C5216	Stainless Steel Tri-Clamp sight glass-1.5" <ul style="list-style-type: none"> • Made of 304 stainless steel & Borosilicate glass • Includes silicone seals and is easily taken apart for cleaning • Attach a cap to one end and then clamp it to the dump valve on a conical fermenter • Makes a great yeast collection cup. 	1.5"	Sight glass
	C5219	Replacement Glass for Tri-Clamp sight glass-1.5" <ul style="list-style-type: none"> • Material: Borosilicate glass • Wall Thickness: 0.312" 	1.5"	Sight glass Replacement
	C5232	Compact Sight Glass <ul style="list-style-type: none"> • Easier to clean than bolted styles • Less cost to repair than bolted styles • Clamp connections standard • Max. Operating Pressure: 100 PSI (6.9 BAR) • Max. Temperature: 200°F (93°C) 		Sight glass

PRODUCT	PART NO.	DESCRIPTION	SIZE	TYPE
	C6619	Stainless Steel Tri-Clover Fitting – 1.5" TC to Male Camlock <ul style="list-style-type: none"> • High grade stainless steel construction • Allows you to connect a female camlock fitting to a 1.5" tri-clover port. • One side has male camlock similar to the type A or F and the other has a 1.5" TC flange. 	1.5"	Tri-Clover
	C6611	TC Compatible cap style reducer from 1.5" X1/2" <ul style="list-style-type: none"> • Material: 304 Stainless Steel • Bore Inside Diameter: 0.375" • Overall Length: 1.375 	1.5" TC	1/2"
	C5226	6" Length Tri Clover Extension Tube (1.5") Also Available in different sizes	6"	TC Extension Tube
	C5227	12"Length Tri Clover Extension Tube(1.5")	12"	
	C5228	18"Length Tri Clover Extension Tube(1.5")	18"	
	C5229	24"Length Tri Clover Extension Tube(1.5")	24"	
	C5230	36"Length Tri Clover Extension Tube(1.5")	36"	