



Draft beer system consists of myriads of components – all brought together and connected using different kinds of caps, clamps, valves, etc. Specialized fittings such as Tri-clover connectors, Quick Disconnect of different types are part of this category along with tail-pieces.

Brewery Fittings

| PRODUCT | PART NO. | DESCRIPTION | SIZE | TYPE | PRODUCT | PART NO. | DESCRIPTION | SIZE | TYPE |
|---------|----------|---|----------------------|---------------------------|---------|----------------|--|--------------------------------|----------------|
| | C6565 | Heavy Duty Stainless Steel Tri-Clover Fitting – 1.5" TC Clamp • Fits 1.5 loch Tri-clamp • Suitable for all other homebrew stuff sanitary fittings; Easy tighten thumb screw • Flange Size: 50.5MM • Does NOT come with silicon gaskets | 1.5" Tri-Clover | 1.5" TC Clamp | | C6612 | TC Tailpiece for 1/2" Vinyl Hose Stainless Steel 304 Connects 1/2" ID vinyl beer line tubing to a coupler or shank. | 1/2" Tube ID | TC Tailpiece |
| | C6566 | Stainless Steel 1/4" Hose Barb to 1.5" TC Cap • Adapter for connecting pipes or fittings of different types • Designed for use with 1/4" ID tubing • Barbed fitting for a tight seal on hoses when used with a hose clamp (not included) | 1/4" OD Hose Barb | Tri-Clover Hose Barb | (PRC) | C6563 | Stainless Steel Camlock Adapter Type F – Male Camlock x 1/2" Male NPT Cam lock cam-and-grows adapter (plug) • One male groove adapter end for connecting to female cam couplers and one NPT female threaded end for connecting to an NPT male threaded connecting (Type F) • No tools are needed | 1/2" Male NPT | Camlock Type F |
| | C6564 | Stainless Steel Tri-Clover Fitting - 1.5" TC x 1/2" Male NPT Barbed Adapter for connecting pipes or fittings of different types - Suitable for 1.5" tri clamp / clover / sanitary fitting - Used for 1/2" Female NPT hardware | 1/2" Male NPT | Tri-Clover NPT Fitting | | C6562 | Stainless Steel Camlock Adapter Type A – Male Camlock x 1/2" Female NPT | 1/2" Female NPT | Camlock Type A |
| | C6613x10 | Tri-Clamp Gasket – 1/2" • Compatible with 1.5" TC hardware | 1.5" Tri-Clover | Tri-Clover Gasket | | C6561 | Stainless Steel Camlock Type C - Female Camlock x 1/2" Barb • Use this barbed fitting to connect onto a male camlock. • Add hose to your barb for quick connecting and disconnecting when you need it. • Barb is 3/8" ID for very little reduction in flow | 1/2" OD Hose Barb (3/8" ID) | Camlock Type C |
| B | C5208 | 1.5" TC Shank for Sampling Beer Faucet • Easily fits with US Tap • Easy to Clean it • Installation is easy and quick also | 1.5" TRI CLAMP | 1.5" TRI CLAMP | | C5233 C5234 | 3" Length Drop-In Thermowell(1.5") • Compatible 3" Tri Clamp Thermowell • Commonly used with 1.5" RIMS tube when a stock sensor that can't be immersed needs to be used • 3/8" Thermowell welded into 1"/1.5" Tri Clover Compatible in different sizes 6" Length Drop-In Thermowell(1.5") | 3" | Thermowell |
| | C5206 | Tri-Clamp Blank Material:Stainless Steel High Pressure Durable Corrosion resistance and high temperature resistance Used for permanent sealing Easy to use Suitable for use in food, beverage, and dairy applications | 1.5" TRI CLAMP | TRI CLAMP | | C5235 C5236 | 12" Length Drop-In Thermowell(1.5") 16" Length Drop-In Thermowell(1.5") | 12" 16" | |
| | | | | | | C5237 | 20" Length Drop-In Thermowell(1.5") | 20" |] |
| | | | | | | | | | |
| | C3587 | Ferrule Gasket For 1.5" Tri-Clover • 1.5" Gasket For Tri-Clover brewery fittings | 1.5" Tri-Clover | 1.5" Tri-Clover | | | | | |