



# Draft Cleaning Kit Ecoline

C2220



## Cleaning kit Instructions

1. Prepare the cleaning solution in a clean bucket by mixing 2 tablespoons of cleaner in half a gallon (~2 litres) of warm water. Also make sure the water is not hot and do not add lye or soap.
2. Open the Cleaning Bottle cap assembly and fill it with the solution. Put the cap back on.
3. Shut off the CO2 tank valve or the air lock on the regulator.
4. Remove the tap from the beer keg. Also remove the beer faucet from the tower using a faucet wrench.  
Next place the beer hose with the tap into the bucket with the remaining cleaning solution. Keep the tap in open position. Insert a ball lifter in order to hold the check valve in that position.
5. Attach the cleaning bottle to the draft beer tower with the fitting washer in place. Hold the jar upside down. You should see the solution flowing into the bucket.

**CAUTION: HOLD THE JAR GENTLY WITHOUT SQUEEZING TO AVOID LEAKING.**

6. Now fill the jar with cool clean water and repeat the steps till clear water flows out.
7. Thoroughly rinse the beer faucet in cold water bucket with a faucet brush.
8. Disconnect the cleaning bottle from the beer tower and assembly back the faucet keeping the washer in place.
9. Reattach the beer keg tap.